

STUDIOMASTER T700 Turntable BASIC

High-end turntable with a unique integrated MC phono preamplifier. Highprecision electronic PLL speed control with contact-free optical sensor. Control panel with backlit touch sensors. Tonearm made of high-grade metals. Delivery without pick-up.



STUDIOMASTER T700

TECHNICAL DATA

Order Number	1.279.005.05	Speed	33 / 45 revolutions per minute
	MC Phono Preamplifier	Speed variation	< 0.1%
Frequency response	7 Hz ... 80 kHz (-3dB)	Connectors	Analogue line output (cinch stereo) DC power socket
Signal-to-noise ratio	- 69 dB (20 Hz ... 20 kHz)	Dimensions	470 x 336 x 156 mm (WxDxH) without sockets
Distortions	0,005 %	Projection (back)	16 mm (hinge, RCA sockets)
Channel offset	0.2 dB	Weight	10.3 kg total 2.85 kg platter (POM) 0.21 kg inner platter (aluminium)
Channel separation	higher 80 dB		
Subsonic filter	10 with first-order high pass (6 dB filter)		
RIAA precision	± 0.2 %		
Impedance matching	6 settings: 47 Ω, 100 Ω, 220 Ω, 470 Ω, 1 kΩ, 2 kΩ		
Input sensitivity	4 settings: 150 µV, 300 µV, 600 µV, 1,2 mV		

ACCESSORIES

	incl.
Solid acrylic glass protective cover	✓
Digital tonearm scale	✓
Record brush	✓
Bubble level	✓
Anti-skating weight	✓
Tonearm counterweight	✓
Turntable belt	✓
White gloves	✓



Accessories in a noble wooden box (incl.)